

Mini kitchen module 6300-ESFS, Right incl. stainless steel sink with 1 bowl. Prepared for hob with 2 cooking zones, width 99 cm



Wall-mounted, motorised mini kitchen module 6300-ESFS contains stainless steel sink with one shallow sink bowl. Prepared for glass ceramic hob with two cooking zones.

The module is available in left or right version.

The modules have a 10 mm shorter width to automatically give 5 mm gap on either side of the unit for the up and down movement. They are also 15 mm shallower in depth to make room for splash protection/tiles.

The anti-pinch strip is placed under the front edge of the worktop. If anything touches the strip, the lift unit stops.

Electronics and motor system "Plug and Play".

The module can be integrated into environments from any kitchen manufacturer.

Functions and advantages

- Motorised wall mounted, adjustable 30 cm
- Adjustable depth 576-606 mm incl. Front
- Tilttable worktop plane for adjustment

The combination includes the following products

Art.no	Description	EAN	Qty
6300HA-099	BASELIFT 6300HA - 99,0 cm	7340193102161	1.00 pcs
385H-099	103 mm Alu-Front, 99.0 cm width		1.00 pcs
61320	Control button for worktop lift - ALU-design - <i>Baselift & Centerlift</i>	7340193105438	1.00 pcs
61360	Safety lock to Baselift	7340193105582	1.00 pcs
6260-005	Fitting kit for cover panels 6260-240 - <i>Baselift & Manulift</i>	7340193108286	1.00 pcs
6260-240	Cover panels, Worktop lifts (59.0-240.0 cm) - <i>Baselift & Manulift</i>	7340193108279	1.00 pcs
6943-06	Rear edge trim ALU for worktop, (per meter)	7340193105520	0.99 m
617ESFS-099	Sit-on sink, mini kitchen, for hob 99.0 cm - GRANBERG ESFS	7340193105247	1.00 pcs
60210	Granberg mixer tap 60210 Incl. dishwasher shut off	7340193105315	1.00 pcs
61800	Flexible water hoses 2-pack, 3/8, length 500mm	7340193105346	1.00 pcs
65220	Cooktop - 30 cm		* 1.00 pcs
** *Not available in this region* **			

Specifications

Installation

Wall

Front height

103 mm

Height adjustment

Motorised, steplessly adjustable 300 mm (700-1000 mm excl. top board)

Speed level

30 mm/sec.

Operation

Control button, ALU-design

Safety

The safety strip is placed under the front edge of the worktop. If anything touches the safety strip, the lifting unit stops

Electrical connection

Plug for 230 V, max 5.0 A

Lifting force

100 kg

IP-class

IP 20

Delivery modules

Ready-mounted worktop incl. safety switch, motors

Frame depth

576 - 606 mm from wall (Incl. front)

Material

Frame:

Aluminum

Cover panels for covering installations under the worktop:

12 mm white melamine. Several colours can be offered upon request.

Fronts:

White lacquered aluminum. Several colours can be offered upon request.

Sink:

Smooth stainless steel sheet. Raised edge around the entire sink.
Thickness: 30 mm

Plumbing connections

Connection is made with flexible hoses

Space to wall / adjoining cabinet

5 mm

Space to wall (for tiles)

15 mm

Tiling

From 700 mm above floor (alternatively all the way down to the floor)

Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.

