

2025-06-17

Draft specification







Hob Module 6350HA-S4, Left incl. worktop. Prepared for hob with 4 cooking zones, width 79 cm Manufacturer: Granberg

The combination includes the following products

Wall mounted, Cranked Height Adjustable Hob Module. Prepared for glass ceramic hob with four cooking zones. Front height is 103 mm.

The module is available in left, centre, or right version.

The modules have a 10 mm shorter width to automatically give 5 mm gap on either side of the unit for the up and down movement. They are also 15 mm shallower in depth to make room for splash protection/tiles.

The module can be integrated into environments from any kitchen manufacturer.

Art.no	Description	EAN	Qty
6350HA-079	MANULIFT 6350HA - 79.0 cm	7340193113532	1.00 pcs
385H-079	103 mm Alu-Front, 79.0 cm width		1.00 pcs
6260-005	Fitting kit for cover panels 6260-240 - Baselift & Manulift	7340193108286	1.00 pcs
6260-240	Cover panels, Worktop lifts (59.0-240.0 cm) - Baselift & Manulift	7340193108279	1.00 pcs
M-BSA	Countertop - Laminate, 450-610 mm depth		0.79 m
6943-06	Rear edge trim ALU for worktop, (per meter)	7340193105520	0.79 m
65201	Cooktop - 60 cm		* 1.00 pcs
	* * *Not available in this region* * *		

Specifications

Installation

Wall

Front height

103 mm

Height adjustment

300 mm height adjustment by a cranked winding handle, (700-1000 mm excl. top board)

Max load

100 kg

Delivery modules

Ready-mounted worktop incl. cranked winding handle.

Frame depth

576 - 606 mm from wall (Incl. front)

Material

Frame:

Aluminum

Cover panels for covering installations under the worktop:

 $12\ mm$ white melamine. Several colours can be offered upon request.

Fronts:

White lacquered aluminum. Several colours can be offered upon request. $% \label{eq:colour_seq}$

Top board:

30 mm worktop in high pressure laminate. Post-shaped front edge. Several colours can be offered upon request.

Space to wall / adjoining cabinet

5 mm

Space to wall (for tiles)

15 mm

Tiling

From 700 mm above floor (alternatively all the way down to the floor)

Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.







