

## **Draft specification**





Sidelift 6400 Combi Module 6400-H2, width 289 cm Manufacturer: Granberg

## The combination includes the following products

Sidelift 6400 combi module, prepared for sink and glass ceramic hob.

The module have hanging cabinets in the outer edges, (40 cm width). The he cabinets can easily be removed to provide space for work done when sitting down. The cabinets can be remounted just as easily.

Safety systems, in the form of safety plates under cabinets and safety strips where there are spaces for knees, stop all movement if any object comes in contact with the switches.

Electronics and motor system "Plug and Play".

Art.no	Description	EAN	Qty
6400HA-289	SIDELIFT 6400HA, 289,0 cm		1.00 pcs
6250-001	Fittings for hanging cabinet	7340193108491	2.00 pcs
760-040-01	Hanging cabinet with drawers, 40.0 cm	7340193108408	1.00 pcs
761-040-01	Hanging cabinet with waste sorting bins, 40.0 cm	7340193108453	1.00 pcs
460-040	Cutlery compartment for inner drawer, 40,0 cm	7340193108514	2.00 pcs
6253-040-01	Safety plate SIDELIFT 6400, Centerlift 6490, 40.0 cm	7340193105605	2.00 pcs
380H-140	MDF-Front 103 mm, 140.0 cm	7340193105896	2.00 pcs
6262-240-01	Cover panels, Sidelift 6400	7340193108293	1.00 pcs
6260-008	Fittings set for cover panels, Sidelift	7340193113914	1.00 pcs
6943-06	Rear edge trim ALU for worktop, (per meter)	7340193105520	2.89 m

## Installation

Floor mounted

#### Height adjustment

Motorised, steplessly adjustable 300 mm (700-1000 mm excl. top board)

## Speed level

20 mm/sec.

#### Operation

Control button, Mini is located in the motor units (left and right side)

#### Safety

There are safety switches under the cabinet and under the front in spaces for knees. The function of the safety switch is to stop the movement if it comes into contact with any object.

#### **Electrical connection**

Plug for 230 V, 2 x 5A

#### **Plumbing connections**

Connection is made with flexible hoses

## Lifting force

400 kg

**IP-class** IP 20

#### Frame depth 561 mm

Front height

#### Dimensions cover plates

Width = Width of lift -410 mm 2 pcs Height 438 mm Thickness 12 mm

#### Width worktop

Width = width of the lift

#### Depth worktop

15 mm shallower than worktops on fixed cabinets

# **Space to wall / adjoining cabinet** 5 mm

### Space to wall (for tiles)

15 mm

#### Tiling

From 700 mm above floor (alternatively all the way down to the floor)

#### **Delivery modules**

1 package with motor units. 1 package with length-dependent beams

#### Material

Motor units in lacquered. Aluminium beams





