

## These products are ETL-listed for the North American market.



Baselift 6600 is a straight, wall-mounted worktop lift with a lifting capacity of 160 kg – ideal even for stone worktops.

The 890 mm width is a good choice when the lift will be fitted with a hob or sink and there is no need for a side work surface.

The frame is supplied in parts to minimise shipping costs and is designed for quick and easy on-site assembly. The installer can also adjust the frame system's width and depth on site.

The open design beneath the worktop provides generous legroom, creating an accessible and comfortable working environment.

Installations beneath the worktop – such as motors, water, and waste pipes – can be easily concealed with telescopic cover panels for a sleek, unified appearance.

The powerful motors operate steplessly, raising and lowering the worktop quickly and quietly, with an integrated safety system that protects against crushing hazards and ensures safe operation.

The lift system is suitable for hobs and sinks with shallow bowls.

Choose between frames and motors in white or anthracite, or fit the lift with fronts from any kitchen manufacturer for a fully integrated design.

### Functions and advantages

- Motor-driven straight worktop lift
- Height adjustable from 700–1000 mm above the floor (excluding worktop)
- Maximum load: 160 kg
- Frame system supplied in parts and available in three widths
- Frame parts can be cut on site to achieve the required width
- Wall-mounted motors
- Frame depth 576–616 mm, adjustable to suit adjacent cabinets
- Centre sections adjustable sideways to fit sink and hob
- Worktop angle adjustable to compensate for uneven walls
- Integrated safety switch
- Available in white or anthracite
- Optional cover panels available to conceal hoses if required

### Useful information

- The worktop depth should be 15 mm shallower than adjacent worktops (to allow a gap for tiling and movement)
- Worktop width = Lift width
- Sinks with a maximum bowl height of 120 mm can be integrated
- Electronics and motor system "Plug and Play"
- Front height: 103 mm
- Cover panels can conceal installations under the worktop  
2 pcs., width = Lift width - 10 mm, height 438 mm, thickness 12-20 mm

## Article Info

Art.no	Description	EAN
6600HAK-089	BASELIFT 6600HA KIT System - 890 mm	

## Mounting

Wall-mounted

## Front height

103 mm

## Height adjustment

Motorised, steplessly adjustable 300 mm (700-1000 mm excl. worktop)

## Speed level

30 mm/sec.

## Operation

Recessed mounted button or radio control

## Safety

A safety strip is mounted underneath the frame of the lifting system. When the strip is activated, the lift unit stops immediately.

## Electrical connection

Plug for 230 V, max 2,9A

## Plumbing connections

Connection is made with flexible hoses

## Lifting force

160 kg

## IP-class

IP 20

## Frame depth

576 – 616 mm from the wall (including integrated front)

## Dimensions cover plates

2 pcs, width = width of the lift -10 mm, height 438 mm, thickness 12-20 mm

## Width worktop

Width = width of the lift

## Depth worktop

565-630 mm (15 mm shallower than worktops on fixed cabinets)

## Space to wall / adjoining cabinet

5 mm

## Space to wall (for tiles)

15 mm

## Tiling

From 700 mm above floor (alternatively all the way down to the floor)

## Delivery modules

Worktop including safety switches and motors. The worktop is final-assembled during installation (front, back panel, and sides are joined together).

## Material

Aluminium frame. White – RAL 9003 powder-coated finish  
Anthracite – AkzoNobel Sablé powder-coated finish (code YW359F)

## Warranty

5 years Warranty

This product comes with a 5-year warranty against manufacturing defects when registered on our website. Without registration, our standard 3-year warranty applies.

