

Draft specification



BASELIFT 6600HA KIT System - 890 mm Manufacturer: Granberg

Article Info

Baselift 6600 is a straight, wall-mounted worktop lift with a lifting capacity of 160 kg – ideal even for stone worktops.

The 890 mm width is a good choice when the lift will be fitted with a hob or sink and there is no need for a side work surface.

The frame is supplied in parts to minimise shipping costs and is designed for quick and easy on-site assembly. The installer can also adjust the frame system's width and depth on site.

The open design beneath the worktop provides generous legroom, creating an accessible and comfortable working environment.

Installations beneath the worktop – such as motors, water, and waste pipes – can be easily concealed with telescopic cover panels for a sleek, unified appearance.

The powerful motors operate steplessly, raising and lowering the worktop quickly and quietly, with an integrated safety system that protects against crushing hazards and ensures safe operation.

The lift system is suitable for hobs and sinks with shallow bowls.

Choose between frames and motors in white or anthracite, or fit the lift with fronts from any kitchen manufacturer for a fully integrated design.

Art.no	Description	EAN
6600HAK-089	BASELIFT 6600HA KIT System - 890 mm	

Mounting

Wall-mounted

Front height

103 mm

Height adjustment

Motorised, steplessly adjustable 300 mm (700-1000 mm excl. worktop)

Speed level

30 mm/sec.

Operation

Recessed mounted button or radio control

Safety

A safety strip is mounted underneath the frame of the lifting system. When the strip is activated, the lift unit stops immediately.

Electrical connection

Plug for 230 V, max 2,9A

Plumbing connections

Connection is made with flexible hoses

Lifting force

160 kg

IP-class

IP 20

Frame depth

576 – 616 mm from the wall (including integrated front)

Dimensions cover plates

2 pcs, width = width of the lift -10 mm, height 438 mm, thickness 12-20 mm

Width worktop

Width = width of the lift

Depth worktop

565-630 mm (15 mm shallower than worktops on fixed cabinets)

Space to wall / adjoining cabinet

5 mm

Space to wall (for tiles)

15 mm

Tiling

From 700 mm above floor (alternatively all the way down to the floor)

Delivery modules

Worktop including safety switches and motors. The worktop is final-assembled during installation (front, back panel, and sides are joined together).

Material

Aluminium frame. White – RAL 9003 powder-coated finish
Anthracite – AkzoNobel Sablé powder-coated finish (code YW359F)

Warranty

5 years Warranty

This product comes with a 5-year warranty against manufacturing defects when registered on our website. Without registration, our standard 3-year warranty applies.

